

ASSEMBLY AND INSTALLATION INSTRUCTIONS

W0149

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements.
2. READ AND SAVE THESE INSTRUCTIONS.





Assembly Instructions:

Turn off the power at fuse or circuit box.

- 1. Attach the threaded pipe to the mounting strap, then secure it with a washer and hex nut.
- 2. Attach the mounting strap to the outlet box by using two mounting screws.
- 3. Pull out the source wires from the outlet box. Make wire connections using wire nuts as follows:
 - ---Connect the hot wire (usually black insulation) from the fixture to the black wire from the power source.
 - ---Connect the neutral wire (usually white insulation) from the fixture to the white wire from the power source.
 - ---Attach the fixture grounding wire (usually bare wire) to the mounting plate with the green grounding screw. Then connect it to the house grounding wire with a wire nut. If your outlet box does not have a house grounding wire, then wrap the fixture grounding wire around the green grounding screw.

Carefully tuck the wires back into the outlet box.


4. Attach the fixture to the mounting strap by inserting the threaded pipe, then secure it with the finial.




- 5. Attach the glass shades onto the glass holders and secure them with the socket rings.
- 6. Install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.

Turn on the power at the main fuse or circuit breaker box.

The following parts are available for re-order if damaged or missing.





A: 30-1/4"

B: 8"

C: 7-1/2"